

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A ~~packet signal for use in a~~ packet communication ~~network~~ apparatus for transmitting a packet to a mobile terminal through ~~[[the]]~~ a packet communication network that includes a plurality of routers inclusive of communication routers configured to communicate with mobile terminals through radio, comprising:
 a destination information unit configured to provide destination information to a
packet inclusive of a description of a state of a mobile terminal that is a state of movement or a state of environment in which the mobile terminal is placed~~[[,]]~~; ~~for transmission of~~
 a transmission unit configured to transmit the packet to one or more mobile terminals having a state that matches ~~said~~ the description of a state of a mobile terminal, said destination information indicating a destination without identifying an address of the destination.

Claim 2 (Currently Amended): The packet ~~signal~~ communication apparatus as claimed in claim 1, wherein said destination information specifies conditions of movement of a mobile terminal.

Claim 3 (Currently Amended): The packet ~~signal~~ communication apparatus as claimed in claim 2, wherein said destination information specifies speed of a mobile terminal.

Claim 4 (Currently Amended): The packet ~~signal~~ communication apparatus as claimed in claim 3, wherein said speed is specified as a single speed.

Claim 5 (Currently Amended): The packet ~~signal~~ communication apparatus as claimed in claim 3, wherein said speed is specified as a plurality of speeds.

Claim 6 (Currently Amended): The packet ~~signal~~ communication apparatus as claimed in claim 3, wherein said speed is specified as a range of speed.

Claim 7 (Currently Amended): A method of controlling packet transfer when packets are transferred to mobile terminals through a packet communication network that includes a plurality of routers inclusive of communication routers configured to communicate with mobile terminals through radio, comprising the steps of:

making any given one of the communication routers keep track of information about conditions of mobile terminals that can communicate with and send said information to said any given one of the communication routers; and

making each of the routers transfer a packet to other routers after checking destination information when the packet, traveling through the packet communication network, includes information inclusive of a description of a state of a mobile terminal that is a state of movement or a state of environment in which the mobile terminal is placed, for transmission of the packet to one or more mobile terminals having a state that matches the description of a state of a mobile terminal, said information indicating a destination without identifying an address of the destination;

making the communication routers transfer the packet through radio to mobile stations that can communicate with the communication routers if the information identifying a packet destination stored in the header portion of the packet matches the information about the conditions of mobile terminals kept track of by the communication routers.

Claim 8 (Previously Presented): The method of controlling packet transfer as claimed in claim 7, wherein the information identifying a packet destination in the header portion of the packet is information about movement of a mobile terminal.

Claim 9 (Previously Presented): The method of controlling packet transfer when packets are transferred to mobile terminals through a packet communication network that includes a plurality of routers inclusive of communication routers configured to communicate with mobile terminals through radio, comprising the steps of:

making any given one of the communication routers keep track of information about conditions of mobile terminals that can communicate with and send said information to said any given one of the communication routers; and

making each of the routers transfer a packet to other routers after checking destination information when the packet, traveling through the packet communication network, includes information about the conditions of mobile terminals stored as the destination information in a header portion thereof; and

making the communication routers transfer the packet through radio to mobile stations that can communicate with the communication routers if the information about the conditions of mobile terminals stored as the destination information in the header portion of the packet matches the information about the conditions of mobile terminals kept track of by the communication routers, wherein

the information about the conditions of mobile terminals kept track of by the communication routers and the information about the conditions of mobile terminals stored as the destination information in the header portion of the packet are information about movement of mobile terminals, and

the information about movement of a mobile terminal specifies speed of a mobile terminal.

Claim 10 (Previously Presented): The method as claimed in claim 9, wherein said speed is specified as a single speed.

Claim 11 (Previously Presented): The method as claimed in claim 9, wherein said speed is specified as a plurality of speeds.

Claim 12 (Previously Presented): The method as claimed in claim 9, wherein said speed is specified as a range of speed.

Claim 13 (Currently Amended): A method of creating a packet, which is transferred to a mobile terminal through a packet communication network that includes a plurality of routers inclusive of communication routers configured to communicate with mobile terminals through radio, comprising the steps of:

specifying a destination of the packet by a state of a mobile terminal; and

generating a packet inclusive of information inclusive of a description of the state of a mobile terminal that is a state of movement or a state of environment in which the mobile terminal is placed, for transmission to one or more mobile terminals having a state that matches the description of the state of a mobile terminal, said information indicating a destination without identifying an address of the destination.